

Cemented Tungsten Carbide and Cermet U

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Revision Date: 05/01/2015 Date of issue: 03/24/2015

Version: 1.0

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Article

Product Name: All k Cemented Tungsten Carbide and Cermet Tools

Synonyms: Carbide Cutting Tools

Intended Use of the Product

Use of the substance/mixture: No additional information available Name, Address, and Telephone of the Responsible Party 1.3.

Company

k u

1.4. Emergency Telephone Number No additional information available

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200]: this product is considered a manufactured article and is not considered a hazard when used in a manner which is consistent with the labeled directions.

2.2. **Label Elements**

GHS-US Labeling

No labeling applicable

Other Hazards 2.3.

During normal operation and usage, cemented carbide products do not present inhalation, ingestion, or other chemical hazards. However, operations such as grinding, cutting, burning, and welding of such products may release dusts, fumes, or vapors which may present health hazards. The health hazards described below relate to these non-routine operations, as well as exposure to component materials.

Wet or dry grinding of cemented carbide products will produce dusts of potentially hazardous ingredients which can be inhaled, swallowed, or come in contact with the skin or eyes. During wet griding, the dust can be suspended or dissolved in the coolant mist.

2.4. **Unknown Acute Toxicity (GHS-US)**

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. **Substance**

Not applicable

3.2. **Mixture**

Name	Product Identifier	%	Classification (GHS-US)
Tungsten carbide	(CAS No) 12070-12-1	10 - 94	Not classified
Titanium carbide (TiC)	(CAS No) 12070-08-5	0.2 - 53	Not classified
Cobalt	(CAS No) 7440-48-4	0 - 20	Acute Tox. 4 (Oral), H302 Acute Tox. 1 (Inhalation:dust,mist), H330 Resp. Sens. 1B, H334 Skin Sens. 1, H317 Carc. 2, H351 Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

05/01/2015 EN (English US) 1/8



MORE YSALS Cemented Tungsten Carbide and Cermet Tools

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Nickel	(CAS No) 7440-02-0	0 - 15	Skin Sens. 1, H317 Carc. 2, H351 STOT RE 1, H372 Aquatic Chronic 3, H412
Tantalum carbide (TaC)	(CAS No) 12070-06-3	0 - 15	Not classified
Niobium carbide (Nb2C)	(CAS No) 12011-99-3	0 - 5	Not classified
Chromium	(CAS No) 7440-47-3	0 - 3	Comb. Dust, H232
Chromium carbide (Cr3C2)	(CAS No) 12012-35-0	0 - 3	Not classified
Aluminum oxide	(CAS No) 1344-28-1	0 - 2	Not classified
Boron oxide (B2O3)	(CAS No) 1303-86-2	0 - 2	Repr. 1B, H360
Zirconium	(CAS No) 7440-67-7	0 - 2	Pyr. Sol. 1, H250 Self-heat. 1, H251 Water-react. 1, H260
Molybdenum	(CAS No) 7439-98-7	0 - 2	Comb. Dust, H232

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice. **First-aid Measures After Inhalation**: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Wash with plenty of soap and water. Obtain medical attention if irritation develops or persists.

First-aid Measures After Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

First-aid Measures After Ingestion: If substantial quantities are swallowed, dilute with large amount of water. Induce vomiting and seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/Injuries: None expected under normal conditions of use.

Symptoms/Injuries After Inhalation: Dust from this product may cause irritation to the respiratory tract.

Symptoms/Injuries After Skin Contact: Dust may cause irritation in skin folds or by contact in combination with tight clothing. Skin exposure can cause an allergic red rash (cobalt itch).

Symptoms/Injuries After Eye Contact: Eye contact with dust may cause mechanical irritation.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Chronic exposure to respirable dust containing cobalt and tungsten carry the potential to cause permanent respiratory diseases, including occupational asthma, interstitial pneumonitis and fibrosis (hard-metal disease), and emphysema. Symptoms include productive cough, wheezing, dyspnea (upon exertion), pleuritic chest pain, and weight loss. Reports outside the industry suggest that ingestion of significant amounts of cobalt can cause blood, heart, and other organ effects. Cobalt metal with tungsten carbide is listed by IARC as Group 2A - probably carcinogenic to humans. Nickel is listed by IARC as Category 2B possibly carcinogenic to humans. Cobalt is listed by ACGIH as an animal carcinogen (A3). Cobalt and nickel are known to the State of California to cause cancer. Nickel is considered reasonably anticipated to be a carcinogen by NTP.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Dusts may present a fire or explosion hazard under rare favoring conditions of particle size, dispersion, concentration, and strong ignition source. However, this is not expected to be a problem under normal handling conditions.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Do not breathe fumes or vapors from fire.

05/01/2015 EN (English US) 2/8



MORE VISALE Cemented Tungsten Carbide and Cermet Tools

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection During Firefighting: For a dust fire confined to a small area, use a respirator approved for toxic dusts and fumes. For a large fire involving this material, fire fighters should use a self-contained breathing apparatus.

Other Information: Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

6.1.1. For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection. **Emergency Procedures:** Eliminate ignition sources. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain and collect as any solid.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Avoid actions that cause dust to become airborne during clean-up such as dry sweeping or using compressed air. Use HEPA vacuum or thoroughly wet with water to clean-up dust. Use PPE described in Section 8. Transfer spilled material to a suitable container for disposal.

6.4. Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Use care during processing to minimize generation of dust. Avoid dust production that exceeds permissible exposure limits.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store in a dry, cool and well-ventilated place.

7.3. Specific End Use(s) No additional information available

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), or OSHA (PEL).

	, , , , , , , , , , , , , , , , , , , ,	
Aluminum ox	kide (1344-28-1)	
USA ACGIH	ACGIH TWA (mg/m³)	10 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust)
		5 mg/m³ (respirable fraction)
Boron oxide	(B2O3) (1303-86-2)	
USA ACGIH	ACGIH TWA (mg/m³)	10 mg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	10 mg/m³
USA IDLH	US IDLH (mg/m³)	2000 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust)
Chromium (7	Chromium (7440-47-3)	
USA ACGIH	ACGIH TWA (mg/m³)	0.5 mg/m³
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.5 mg/m³
USA IDLH	US IDLH (mg/m³)	250 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	1 mg/m³
Cobalt (7440-	-48-4)	
USA ACGIH	ACGIH TWA (mg/m³)	0.02 mg/m³
USA ACGIH	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.05 mg/m³ (dust and fume)
USA IDLH	US IDLH (mg/m³)	20 mg/m³ (dust and fume)
USA OSHA	OSHA PEL (TWA) (mg/m³)	0.1 mg/m³ (dust and fume)

05/01/2015 EN (English US) 3/8



MORE VISALS Cemented Tungsten Carbide and Cermet Tools

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Nickel (7440-	02-0)		
USA ACGIH	ACGIH TWA (mg/m³)	1.5 mg/m³ (inhalable fraction)	
USA ACGIH	ACGIH chemical category	Not Suspected as a Human Carcinogen	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.015 mg/m³	
USA IDLH	US IDLH (mg/m³)	10 mg/m³	
USA OSHA	OSHA PEL (TWA) (mg/m³)	1 mg/m³	
Zirconium (7	Zirconium (7440-67-7)		
USA ACGIH	ACGIH TWA (mg/m³)	5 mg/m³	
USA ACGIH	ACGIH STEL (mg/m³)	10 mg/m³	
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	5 mg/m ³	
USA NIOSH	NIOSH REL (STEL) (mg/m³)	10 mg/m³	
USA IDLH	US IDLH (mg/m³)	50 mg/m ³	
Molybdenum	Molybdenum (7439-98-7)		
USA ACGIH	ACGIH TWA (mg/m³)	10 mg/m³ (inhalable fraction)	
		3 mg/m³ (respirable fraction)	
USA IDLH	US IDLH (mg/m³)	5000 mg/m³	

8.2. Exposure Controls

Appropriate Engineering Controls : Use local exhaust or general dilution ventilation or other suppression methods to

maintain dust levels below exposure limits. Power equipment should be equipped with proper dust collection devices. Ensure all national/local regulations are

observed.

Personal Protective Equipment : Not generally required. The use of personal protective equipment may be

necessary as conditions warrant.

Materials for Protective Clothing : Chemically resistant materials and fabrics.

Hand Protection : Chemically resistant gloves are recommended, but not required.

Eye Protection : Chemical safety goggles.

Skin and Body Protection : Wear suitable protective clothing.

Respiratory Protection : If exposure limits are exceeded or irritation is experienced, approved respiratory

protection should be worn.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Partition Coefficient: N-Octanol/Water

Viscosity

9.1. Information on Basic Physical and Chemical Properties

Physical State: SolidAppearance: Dark GrayOdor: Odorless

Odor Threshold No data available : No data available **Evaporation Rate** : No data available : 5045 °C (9113 °F) **Melting Point Freezing Point** : No data available **Boiling Point** No data available Flash Point : No data available : No data available **Auto-ignition Temperature Decomposition Temperature** No data available Flammability (solid, gas) : No data available No data available Vapor Pressure Relative Vapor Density at 20 °C : No data available **Relative Density** : 10 - 15 (water=1) Solubility : Insoluble.

05/01/2015 EN (English US) 4/8

No data available

: No data available



RUSHMORE USALS Cemented Tungsten Carbide and Cermet Tools

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other Information No additional information available

SECTION 10: STABILITY AND REACTIVITY

- **Reactivity:** Hazardous reactions will not occur under normal conditions. 10.1.
- 10.2. **Chemical Stability:** Stable at standard temperature and pressure.
- 10.3. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid: Not available
- Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Contact of dust with strong oxidizers may cause 10.5. fire or explosion.
- 10.6. Hazardous Decomposition Products: Oxides of aluminum. Oxides of cobalt. Oxides of titanium. Oxides of tungsten. Carbon oxides (CO, CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

Information On Toxicological Effects 11.1.

Acute Toxicity: Not classified

Aluminum oxide (1344-28-1)	
LD50 Oral Rat	> 15900 mg/kg
LC50 Inhalation Rat	> 2.3 mg/l/4h
Chromium (7440-47-3)	
LD50 Oral Rat	> 5000 mg/kg
Cobalt (7440-48-4)	
LD50 Oral Rat	215.9 - 1140 mg/kg
LC50 Inhalation Rat	> 10 mg/l (Exposure time: 1 h)
Nickel (7440-02-0)	
LD50 Oral Rat	> 9000 mg/kg
Molybdenum (7439-98-7)	
LD50 Oral Rat	> 2000 mg/kg
LD50 Dermal Rat	> 2000 mg/kg

Skin Corrosion/Irritation: Not classified Serious Eye Damage/Irritation: Not classified Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified Carcinogenicity: Not classified

Chromium (7440-47-3)	
IARC group	3
Cobalt (7440-48-4)	
IARC group	2B
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Nickel (7440-02-0)	
IARC group	2B
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Dust from this product may cause irritation to the respiratory tract.

Symptoms/Injuries After Skin Contact: Dust may cause irritation in skin folds or by contact in combination with tight clothing.

Symptoms/Injuries After Eye Contact: Eye contact with dust may cause mechanical irritation. Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

SECTION 12: ECOLOGICAL INFORMATION

12.1. **Toxicity**

Aluminum oxide (1344-28-1)	
LC50 Fish 1	> 100 mg/l

05/01/2015 EN (English US)



MORE VISALS Cemented Tungsten Carbide and Cermet Tools

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EC50 Daphnia 1	> 100 mg/l
ErC50 (algae)	> 100 mg/l
NOEC (acute)	> 50 mg/l
Boron oxide (B2O3) (1303-86-2)	
EC50 Daphnia 1	370 - 490 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Nickel (7440-02-0)	
LC50 Fish 1	100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio)
EC50 Daphnia 1	13 (13 - 200) μg/l (Exposure time: 48h - Species: Ceriodaphnia dubia [static])
LC 50 Fish 2	1.3 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])
EC50 Daphnia 2	1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 Other Aquatic Organisms 2	0.174 (0.174 - 0.311) mg/l (Exposure time: 96 h - Species: Pseudokirchneriella
	subcapitata [static])

12.2. Persistence and Degradability No additional information available

12.3. Bioaccumulative Potential

Cobalt (7440-48-4)	
BCF fish 1	(no bioaccumulation)

- 12.4. Mobility in Soil No additional information available
- 12.5. Other Adverse Effects

No additional information available

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

SECTION 14: TRANSPORT INFORMATION

- **14.1.** In Accordance with DOT Not regulated for transport
- 14.2. In Accordance with IMDG Not regulated for transport
- 14.3. In Accordance with IATA Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1 US Federal Regulations

13.1 US rederal Regulations		
Aluminum oxide (1344-28-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Listed on United States SARA Section 313		
SARA Section 313 - Emission Reporting	1.0 % (fibrous forms)	
Boron oxide (B2O3) (1303-86-2)		
Listed on the United States TSCA (Toxic Substances Cont	trol Act) inventory	
Chromium (7440-47-3)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Listed on United States SARA Section 313		
SARA Section 313 - Emission Reporting 1.0 %		
Chromium carbide (Cr3C2) (12012-35-0)		
Listed on the United States TSCA (Toxic Substances Cont	trol Act) inventory	
Cobalt (7440-48-4)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Listed on United States SARA Section 313		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	
	Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting	0.1 %	
Nickel (7440-02-0)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Listed on United States SARA Section 313		
RQ (Reportable quantity, section 304 of EPA's List of	100 lb (only applicable if particles are < 100 μm)	
Lists)		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	

05/01/2015 EN (English US) 6/8



HMORE WALL Cemented Tungsten Carbide and Cermet Tools

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting	0.1 %	
Niobium carbide (Nb2C) (12011-99-3)		
Listed on the United States TSCA (Toxic Substance	es Control Act) inventory	
Tantalum carbide (TaC) (12070-06-3)		
Listed on the United States TSCA (Toxic Substance	es Control Act) inventory	
Titanium carbide (TiC) (12070-08-5)		
Listed on the United States TSCA (Toxic Substance	es Control Act) inventory	
Tungsten carbide (12070-12-1)		
Listed on the United States TSCA (Toxic Substance	es Control Act) inventory	
Zirconium (7440-67-7)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Molybdenum (7439-98-7)		-
Listed on the United States TSCA (Toxic Substance	es Control Act) inventory	

15.2 US State Regulations

Cobalt (7440-48-4)	
U.S California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of
	California to cause cancer.
Nickel (7440-02-0)	
U.S California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of
	California to cause cancer.

Aluminum oxide (1344-28-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Boron oxide (B2O3) (1303-86-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Chromium (7440-47-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances
- U.S. Pennsylvania RTK (Right to Know) List

Cobalt (7440-48-4)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Nickel (7440-02-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances
- U.S. Pennsylvania RTK (Right to Know) List

Tungsten carbide (12070-12-1)

U.S. - New Jersey - Right to Know Hazardous Substance List

Zirconium (7440-67-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Molybdenum (7439-98-7)

05/01/2015 EN (English US) 7/8



SHMORE WALL Cemented Tungsten Carbide and Cermet Tools

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 05/01/2015

This document has been prepared in accordance with the SDS Other Information

requirements of the OSHA Hazard Communication Standard 29 CFR

1910.1200.

GHS Full Text Phrases:

	_
Acute Tox. 1 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 1
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Carc. 2	Carcinogenicity Category 2
Comb. Dust	Combustible Dust
Pyr. Sol. 1	Pyrophoric solids Category 1
Repr. 1B	Reproductive toxicity Category 1B
Repr. 2	Reproductive toxicity Category 2
Resp. Sens. 1B	Respiratory sensitisation Category 1B
Self-heat. 1	Self-heating substances and mixtures Category 1
Skin Sens. 1	Skin sensitization Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
Water-react. 1	Substances and mixtures which in contact with water emit flammable
	gases Category 1
H232	May form combustible dust concentrations in air
H250	Catches fire spontaneously if exposed to air
H251	Self-heating: may catch fire
H260	In contact with water releases flammable gases which may ignite
	spontaneously
H302	Harmful if swallowed
H317	May cause an allergic skin reaction
H330	Fatal if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if
	inhaled
H351	Suspected of causing cancer
H360	May damage fertility or the unborn child
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)

05/01/2015 EN (English US) 8/8