


1. PRODUCT & COMPANY IDENTIFICATION

1.1	Product Name:	TOOL BLACK® GEL
1.2	Chemical Name:	Acid Mixture
1.3	Synonyms:	45311, 45328
1.4	Trade Names:	Tool Black® Gel
1.5	Product Use:	Blackening Solution for Iron and Steel
1.6	Distributor's Name:	Precision Brand Products, Inc.
1.7	Distributor's Address:	2250 Curtiss Street, Downers Grove IL 60515 USA
1.8	Emergency Phone:	ChemTrec +1 (800) 424-9300 / +1 (703) 527-3887 or Poison Control Center +1 (855) 281-1742
1.9	Business Phone / Fax:	+1 (630) 969-7200 / +1 (630) 969-0310

2. HAZARDS IDENTIFICATION

2.1	Hazard Identification:	<p>This product is classified as a hazardous substance and as dangerous goods according to the classification criteria of [NOHSC: 1088 (2004)] and ADG Code (Australia).</p> <p>DANGER! TOXIC IF SWALLOWED. MAY CAUSE SEVERE SKIN BURNS OR EYE DAMAGE. MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE. MAY INTENSIFY FIRE; OXIDIZER.</p> <p><u>Classification:</u> Acute Toxicity-Inh 3; Skin Corrosion 1A; Oxidizing Liquid 3</p> <p><u>Hazard Statements (H):</u> H301 – Toxic if swallowed. H314 – Causes severe skin burns and eye damage. H373 – May cause damage to organs through prolonged or repeated exposure. H272 – May intensify fire; oxidizer. H410 – Very toxic to aquatic life with long lasting effects.</p> <p><u>Precautionary Statements (P):</u> P220 – Keep/Store away from clothing/ combustible materials. P273 – Avoid release to the environment. P280 – Wear protective gloves/ protective clothing/ eye protection/ face protection. P301+P310 – IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501 – Dispose of contents/ container to an approved waste disposal plant.</p>	
-----	------------------------	--	---

3. COMPOSITION & INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)									OTHER
					ACGIH		NOHSC			OSHA				
					TLV	STEL	ppm	ppm	ppm	TLV	STEL	IDLH		
WATER	7732-18-5	ZC0110000	231-791-2	60-100	NE	NE	NF	NF	NF	NE	NE	NE		
POLYOXYETHYLENE STEARYL WAX DERIVATIVES	9005-00-9	NA	500-017-8	7-13	NA	NA	NF	NF	NF	NA	NA	NA		
CUPRIC SULFATE	7758-99-8	NA	NA	5-10	(1)	NA	NF	NF	NF	(1)	NA	1000		
SELENIOS ACID	7783-00-8	VS7175000	231-974-7	1-5	(0.2)	NA	(0.2)	NF	NF	(0.2)	NA	NA		
NITRIC ACID	7697-37-2	QU5775000	231-714-2	1-5	2	4	2	NF	NF	2	NA	25		

4. FIRST AID MEASURES

4.1	First Aid:	<p><u>Ingestion:</u> DO NOT INDUCE VOMITING. Contact SafetyCall +1 (855) 281-1742 or the nearest Poison Control Center or local emergency telephone number for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.</p> <p><u>Eyes:</u> If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately.</p> <p><u>Skin:</u> Remove contaminated clothing and wash affected areas with soap and water. If discomfort persists and/or the skin reaction worsens, contact a physician immediately. Do not wear contaminated clothing until after it has been properly cleaned.</p> <p><u>Inhalation:</u> Remove victim to fresh air at once. Under extreme conditions, if breathing stops, perform artificial respiration. Seek immediate medical attention.</p>
4.2	Effects of Exposure:	<p><u>Eyes:</u> Severe or permanent eye damage.</p> <p><u>Skin:</u> Burns upon direct contact.</p> <p><u>Ingestion:</u> Severe burns of mouth, throat, stomach.</p> <p><u>Inhalation:</u> Severe irritation or burns in respiratory tract and mucous membranes. Possible lung damage.</p>

4. FIRST AID MEASURES – cont'd

4.3	Symptoms of Overexposure:	Eyes: Redness, burning, irritation, and swelling around eyes Skin: Redness, burning, itching, rash, blistering of skin. Ingestion: Nausea, vomiting, severe abdominal pain. Inhalation: Coughing, wheezing, swelling of throat, irritation in mucous membranes, difficulty breathing.
4.4	Acute Health Effects:	May be harmful if inhaled. Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract. May be harmful if swallowed. Causes burns. May be harmful if absorbed through skin.
4.5	Chronic Health Effects:	May damage the nervous system, kidney and/or liver.
4.6	Target Organs:	Eyes, Skin, Nervous System, Kidneys, Liver, Respiratory System.
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions, and disorders of the target organs (eyes, skin, and respiratory system) or impaired kidney function may be more susceptible to the effects of this substance.

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARDS	2
PROTECTIVE EQUIPMENT	
EYES	SKIN
LUNGS	H

5. FIREFIGHTING MEASURES

5.1	Fire & Explosion Hazards:	Non-flammable. May react with metals to release hydrogen gas, which can form explosive mixtures with air. May intensify fire; oxidizer.	
5.2	Extinguishing Methods:	Use fire-extinguishing media appropriate for surrounding materials.	
5.3	Firefighting Procedures:	As with any fire, firefighters should wear appropriate protective equipment including a MSHA/NIOSH approved or equivalent self-contained breathing apparatus (SCBA) and protective clothing. Fight fires as for surrounding materials. Hazardous decomposition products may be released. Thermal degradation may produce oxides of carbon, phosphorous, selenium and/or nitrogen, hydrocarbons and/or derivatives. Fire should be fought from a safe distance. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway.	

6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment (PPE). Use safety glasses or safety goggles and face shield; use gloves and other protective clothing (e.g., apron, boots, etc.) to prevent skin contact. <u>Small Spills:</u> Wear appropriate protective equipment including gloves and protective eyewear. Use a non-combustible, inert material such as vermiculite or sand to soak up the product and place into a container for later disposal. <u>Large Spills:</u> Keep incompatible materials (e.g., organics such as oil) away from spill. Stay upwind and away from spill or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant. Recover as much free liquid as possible and collect in acid-resistant container. Use absorbent to pick up residue. Avoid discharging liquid directly into a sewer or surface waters.
-----	---------	--




7. HANDLING & STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Avoid breathing mists or spray. Avoid eye and skin contact. Wear protective equipment when handling product. Keep out of the reach of children. Do not eat, drink or smoke when handling this product. Wash thoroughly after handling. Do not expose to heat and flame. Use only in ventilated areas. Keep out of the reach of children. Immediately clean-up and decontaminate any spills or residues.
7.2	Storage & Handling:	Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Store in acid-resistant containers. Keep containers covered when not in use. Avoid temperatures above 40 °C (120 °F). Keep away from incompatible substances (see Section 10). Protect containers from physical damage.
7.3	Special Precautions:	Empty containers may retain hazardous product residues.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Exposure Limits: ppm (mg/m ³)		ACGIH		NOHSC			OSHA			OTHER
		CHEMICAL NAME(S)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		SELENIOS ACID	(0.2)	NA	(0.2)	NF	NF	(0.2)	NA	NA	
		NITRIC ACID	2	4	2	NF	NF	2	NA	25	
		CUPRIC SULFATE	(1)	NA	NF	NF	NF	(1)	NA	1000	
8.2	Ventilation & Engineering Controls:	Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).									
8.3	Respiratory Protection:	In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.									

8. EXPOSURE CONTROLS & PERSONAL PROTECTION – cont'd

8.4	Eye Protection:	Safety glasses with side shields must be used when handling or using this product. A protective face shield is also recommended.	
8.5	Hand Protection:	Wear protective, chemical-resistant gloves (e.g., neoprene) when using or handling this product.	
8.6	Body Protection:	A chemical resistant apron and/or protective clothing are recommended when handling or using this product.	

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Appearance:	Viscous blue liquid
9.2	Odor:	Odorless
9.3	Odor Threshold:	0.29 to 0.98 ppm (Nitric Acid)
9.4	pH:	1.0
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	> 100 °C (> 212 °F)
9.7	Flashpoint:	Wax: 207 °C (405 °F) COC
9.8	Upper/Lower Flammability Limits:	NA
9.9	Vapor Pressure:	NA
9.10	Vapor Density:	< 1.0 (air = 1.0)
9.11	Relative Density:	1.017
9.12	Solubility:	Insoluble (water); Soluble (isopropanol)
9.13	Partition Coefficient (log P _{ow}):	NA
9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	NA
9.17	Other Information:	Evaporation Rate: < 1.0 (ethyl ether = 1.0)

10. STABILITY & REACTIVITY

10.1	Stability:	Stable at normal temperatures.
10.2	Hazardous Decomposition Products:	Reaction with organics and strong reducing agents can produce organoselenides and hydrogen selenide. Thermal decomposition may produce selenium, nitrogen, phosphoric and copper oxides.
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Excessive heat, shock, friction.
10.5	Incompatible Substances:	Cyanides, water-reactive substances, strong reducing agents, chlorinated cleaners or sanitizers, combustible organic materials, most metals.

11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: YES	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	Cupric Sulfate: LD ₅₀ (oral, rat) = 300 mg/kg		
11.3	Acute Toxicity:	See Section 2.4		
11.4	Chronic Toxicity:	See Section 2.5		
11.5	Suspected Carcinogen:	Components in this product are listed by IARC as Group 3 (Not classifiable as to its carcinogenicity to humans)		
11.6	Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans.		
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.		
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.		
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.		
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.		
11.7	Irritancy of Product:	See Section 2.3		
11.8	Biological Exposure Indices:	NE		
11.9	Physician Recommendations:	Treat symptomatically.		


12. ECOLOGICAL INFORMATION

12.1	Environmental Stability:	No data available.
12.2	Effects on Plants & Animals:	No data available.
12.3	Effects on Aquatic Life:	Very toxic to aquatic life with long lasting effects. Phosphoric Acid: EC ₅₀ (Daphnia magna, 12h) = 4.6 mg/L



13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal:	Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations. Contact the appropriate agency for specific information. Treatment, transport, storage and disposal of hazardous waste must be provided by a licensed facility or waste hauler.
13.2	Special Considerations:	U.S. EPA Hazardous Waste – Characteristic - Corrosive (D002), Characteristic - Toxic (D010)

14. TRANSPORTATION INFORMATION

14.1	49 CFR (GND):	UN3264, CORROSIVE LIQUIDS, ACIDIC, INORGANIC, N.O.S. (SELENIOS ACID, PHOSPHORIC ACID), 8, II, (LTD QTY, IP VOL ≤ 5.0 L)	
14.2	IATA (AIR):	UN3264, CORROSIVE LIQUIDS, ACIDIC, INORGANIC, N.O.S. (SELENIOS ACID, PHOSPHORIC ACID), 8, II, (LTD QTY, IP VOL ≤ 0.5 L)	
14.3	IMDG (OCN):	UN3264, CORROSIVE LIQUIDS, ACIDIC, INORGANIC, N.O.S. (SELENIOS ACID, PHOSPHORIC ACID), 8, II, (LTD QTY, IP VOL ≤ 5.0 L)	
14.4	TDGR (Canadian GND):	UN3264, CORROSIVE LIQUIDS, ACIDIC, INORGANIC, N.O.S. (SELENIOS ACID, PHOSPHORIC ACID), 8, II, (LTD QTY, IP VOL ≤ 5.0 L)	
14.5	ADR/RID (EU):	UN3264, CORROSIVE LIQUIDS, ACIDIC, INORGANIC, N.O.S. (SELENIOS ACID, PHOSPHORIC ACID), 8, II, (LTD QTY, IP VOL ≤ 5.0 L)	
14.6	SCT (MEXICO):	UN3264, LIQUIDOS, CORROSIVOS, ACIDO, INORGANICO, N.E.P. (ACIDO SELENIO, ACIDO FOSFORICO), 8, II, (CANTIDAD LIMITADA, IP VOL ≤ 5.0 L)	
14.7	ADGR (AUS):	UN3264, CORROSIVE LIQUIDS, ACIDIC, INORGANIC, N.O.S. (SELENIOS ACID, PHOSPHORIC ACID), 8, II, (LTD QTY, IP VOL ≤ 5.0 L)	

15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements:	This product contains <u>Nitric Acid</u> , <u>Cupric Sulfate</u> and <u>Selenious Acid</u> , substances subject to SARA Title III, section 313 reporting requirements.	
15.2	SARA Threshold Planning Quantity:	302 TPQ (Nitric Acid): 1,000 lbs (454 kg)	
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.	
15.4	CERCLA Reportable Quantity (RQ):	<u>Selenious Acid</u> : 10 lbs (4.54 kg); <u>Nitric Acid</u> : 1,000 lbs (454 kg); <u>Cupric Sulfate</u> : 10 lbs (4.54 kg)	
15.5	Other Federal Requirements:	NA	
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS Class E (Corrosive Material). WHMIS Class D1 (Materials Causing Immediate and Serious Toxic Effects).	
15.7	State Regulatory Information:	<p><u>Selenious Acid</u> is found on the following state criteria lists: Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), Pennsylvania Right-to-Know List (PA), and Wisconsin Hazardous Substances List (WI).</p> <p><u>Nitric Acid</u> is found on the following state criteria lists: FL, MA, MN, New Jersey Right-to-Know List (NJ), PA, and Washington Permissible Exposures List (WA).</p> <p>No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).</p>	
15.8	Other Requirements:	<p>The primary components of this product are listed in Annex I of EU Directive 67/548/EEC.</p> <p><u>Selenious Acid</u>: Corrosive (C), Toxic (T). <u>Risk Phrases</u> (R): R35 – Causes severe burns. <u>Safety Phrases</u> (S): S1/2-7/9-24/25-26-28-46 - Keep locked up and out of the reach of children. Keep container tightly closed and in a well-ventilated place. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash with plenty of soap and warm water. If swallowed, seek medical advice immediately and show this container or label.</p>	

16. OTHER INFORMATION

16.1	Other Information:	DANGER! POISON. CORROSIVE. May be fatal if swallowed or harmful if inhaled. Causes severe burns to eyes and skin. OXIDIZER. Combustible materials that contact this product may ignite more easily and burn more intensely. Avoid shock, heat, and friction.	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Precision Brand Products Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.	
16.4	Prepared for:	Precision Brand Products, Inc. 2250 Curtiss Street Downers Grove, IL 60515 USA Tel: +1 (630) 969-7200 Fax: +1 (630) 969-0310 http://www.precisionbrand.com	 PRECISION BRAND
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com	 <i>Dangerous Goods Training & Consulting</i>

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
----------------	----------------------------------

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
IDLH	Immediately Dangerous to Life and Health

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
------------	--

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

HEALTH
FLAMMABILITY
PHYSICAL HAZARDS
PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

A		G	
B		H	
C		I	
D		J	
E		K	
F		X	Consult your supervisor or SOPs for special handling directions.

Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves
Boots	Synthetic Apron	Protective Clothing & Full Suit	Dust Respirator
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus
Flam.	Flammable
Liq.	Liquid
Sol.	Solid
Tox.	Toxicity
Irrit.	Irritation
Sens.	Sensitization
Ox.	Oxidizing
Corr.	Corrosion
Repr.	Reproductive (Harm)
Asp.	Aspiration
Inh.	Inhalation
Dam.	Damage
STOT SE	Specific Target Organ Toxicity – Single Exposure
STOT RE	Specific Target Organ Toxicity – Repeated Exposure

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:	
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD₀₁	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD₀₁, LD₀₁, & LD₀₂ or TC, TC₀₁, LC₀₁, & LC₀₂	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL_m	Median threshold limit
log K_{ow} or log K_{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

C	E	F	N	O	T	Xi	Xn
Corrosive	Explosive	Flammabl e	Harmful	Oxidizing	Toxic	Irritant	Harmful


CLP/GHS (1272/2008/EC) PICTOGRAMS:

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment

1. PRODUCT & COMPANY IDENTIFICATION

1.1	Product Name:	METAL POLISH/CLEANSER
1.2	Chemical Name:	Aqueous Solution
1.3	Synonyms:	45118, 45106
1.4	Trade Names:	Metal Polish/Cleanser
1.5	Product Use:	Metal Polish/Cleanser
1.6	Distributor's Name:	Precision Brand Products, Inc.
1.7	Distributor's Address:	2250 Curtiss Street, Downers Grove IL 60515 USA
1.8	Emergency Phone:	ChemTrec +1 (800) 424-9300 / +1 (703) 527-3887 or Poison Control Center +1 (855) 281-1742
1.9	Business Phone / Fax:	+1 (630) 969-7200 / +1 (630) 969-0310

2. HAZARDS IDENTIFICATION

2.1	Hazard Identification:	<p>This product is classified as a hazardous substance but not as dangerous goods according to the classification criteria of [NOHSC: 1088 (2004)] and ADG Code (Australia).</p> <p>WARNING! MAY BE HARMFUL IN CONTACT WITH SKIN. CAUSES SKIN IRRITATION. CAUSES EYE IRRITATION.</p> <p><u>Classification:</u> Acute Tox. Dermal 5; Skin Irrit. 2; Eye Irrit</p> <p><u>Hazard Statements (H):</u> H313 – May be harmful in contact with skin. H315 – Causes skin irritation. H320 – Causes eye irritation.</p> <p><u>Precautionary Statements (P):</u> P261 – Avoid breathing mist/sprays. P272 – Contaminated work clothing should not be allowed out of the workplace. P280 – Wear protective gloves/eye protection. P302+P352 – IF ON SKIN: Wash with plenty of soap and water. P333+P313 – If skin irritation or rash occurs: Get medical advice/attention. P321 – Specific treatment – see section 4 of this Safety Data Sheet. P363 Wash contaminated clothing before reuse. P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501 – Dispose of contents/container to licensed treatment, storage and disposal facility (TSDF).</p>	
-----	------------------------	---	---

3. COMPOSITION & INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)									OTHER
					ACGIH		NOHSC			OSHA				
					ppm		ppm			ppm				
					TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	TLV	STEL	IDLH		
WATER	7732-18-5	NA	231-791-2	60-100	NE	NE	NF	NF	NF	NE	NE	NE		
MODIFIED ALKANOLAMIDE	8051-30-7	NA	232-483-0	1-5	NA	NA	NF	NF	NF	NA	NA	NA		
SODIUM TETRABORATE	1303-96-4	VZ2275000	NA	1-5	(2)	(6)	NF	NF	NF	(2)	NA	Na	(1) NIOSH	
SODIUM PYROPHOSPHATE DIBASIC	7758-16-9	UX6475000	231-835-0	1-5	NA	NA	NF	NF	NF	NA	NA	NA		
SODIUM XYLENE SULFONATE	1300-72-7	ZE5100000	215-090-9	1-5	NA	NA	NF	NF	NF	NA	NA	NA		

4. FIRST AID MEASURES

4.1	First Aid:	<p><u>Ingestion:</u> DO NOT INDUCE VOMITING. Contact ChemTrec +1 (800) 424-9300 or the nearest Poison Control Center or local emergency telephone number for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.</p> <p><u>Eyes:</u> If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately.</p> <p><u>Skin:</u> Remove contaminated clothing and wash affected areas with soap and water. If discomfort persists and/or the skin reaction worsens, contact a physician immediately. Do not wear contaminated clothing until after it has been properly cleaned.</p> <p><u>Inhalation:</u> Remove victim to fresh air at once. Under extreme conditions, if breathing stops, perform artificial respiration. Seek immediate medical attention.</p>
4.2	Effects of Exposure:	<p><u>Eyes:</u> Irritation upon direct contact.</p> <p><u>Skin:</u> Mildly irritating. Prolonged or repeated skin contact can result in drying and defatting of the skin, and possible sensitization in some individuals.</p> <p><u>Ingestion:</u> Irritation to the gastrointestinal tract. This material can enter the lungs during swallowing or vomiting and cause lung damage.</p> <p><u>Inhalation:</u> Irritation of respiratory tract and mucous membranes.</p>

4. FIRST AID MEASURES – cont'd

4.3	Symptoms of Overexposure:	<p>Eyes: Redness, burning, irritation, stinging and swelling around eyes. Skin: Redness, burning, itching, rash, drying and defatting of the skin. Ingestion: Nausea, vomiting, severe abdominal pain. Inhalation: Coughing, wheezing, swelling of throat, irritation in mucous membranes, difficulty breathing.</p>													
4.4	Acute Health Effects:	Irritation or possible burns upon direct skin contact. Possible irreversible damage to eyes. Irritation and possible sensitization with certain individuals.													
4.5	Chronic Health Effects:	Irritation and possible skin sensitization with certain individuals. Prolonged or repeated skin exposure may cause dermatitis.													
4.6	Target Organs:	Eyes, Skin, Lungs (severe irritant).													
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions, and disorders of the target organs (eyes, skin, and respiratory system).	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="background-color: #0000FF; color: white;">HEALTH</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: #FF0000; color: white;">FLAMMABILITY</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="background-color: #FFA500; color: white;">PHYSICAL HAZARDS</td> <td style="text-align: center;">0</td> </tr> <tr> <td colspan="2">PROTECTIVE EQUIPMENT</td> </tr> <tr> <td>EYES</td> <td>SKIN</td> </tr> <tr> <td></td> <td></td> </tr> </table>	HEALTH	1	FLAMMABILITY	0	PHYSICAL HAZARDS	0	PROTECTIVE EQUIPMENT		EYES	SKIN		
HEALTH	1														
FLAMMABILITY	0														
PHYSICAL HAZARDS	0														
PROTECTIVE EQUIPMENT															
EYES	SKIN														

5. FIREFIGHTING MEASURES

5.1	Fire & Explosion Hazards:	Non-flammable. Use media as appropriate for surrounding fire.	
5.2	Extinguishing Methods:	Carbon Dioxide, Foam, Water Spray, Halon (if permitted), Dry Chemical Extinguisher.	
5.3	Firefighting Procedures:	As with any fire, firefighters should wear appropriate protective equipment including a MSHA/NIOSH approved or equivalent self-contained breathing apparatus (SCBA) and protective clothing. Hazardous decomposition products may be released. Thermal degradation may produce oxides of carbon, and/or nitrogen, hydrocarbons and/or derivatives. Fire should be fought from a safe distance. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway.	

6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	<p>Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment (PPE). Use safety glasses or safety goggles and face shield; use gloves and other protective clothing (e.g., apron, boots, etc.) to prevent skin contact.</p> <p>Small Spills: Wear appropriate protective equipment including gloves and protective eyewear. Use a non-combustible, inert material such as vermiculite or sand to soak up the product and place into a container for later disposal.</p> <p>Large Spills: Keep incompatible materials (e.g., organics such as oil) away from spill. Stay upwind and away from spill or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant. Recover as much free liquid as possible and collect in acid-resistant container. Use absorbent to pick up residue. Avoid discharging liquid directly into a sewer or surface waters.</p>	
-----	---------	---	--

7. HANDLING & STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Avoid breathing mists or spray. Avoid eye and skin contact. Wear protective equipment when handling product. Keep out of the reach of children. Do not eat, drink or smoke when handling this product. Wash thoroughly after handling. Immediately clean-up and decontaminate any spills or residues.	
7.2	Storage & Handling:	Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Keep away from incompatible substances (see Section 10). Protect containers from physical damage.	
7.3	Special Precautions:	Empty containers may retain hazardous product residues.	

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Exposure Limits: ppm (mg/m ³)		ACGIH		NOHSC			OSHA			OTHER	
		CHEMICAL NAME(S)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH		
		SODIUM TETRABORATE	(2)	(6)	NF	NF	NF	(2)	NA	Na	(1) NIOSH	
8.2	Ventilation & Engineering Controls:	Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).										
8.3	Respiratory Protection:	In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia (e.g., NIOSH approved respirator with full or half-face N95 cartridge)										
8.4	Eye Protection:	Safety glasses with side shields must be used when handling or using this product. A protective face shield is also recommended.										
8.5	Hand Protection:	Wear protective, chemical-resistant gloves (e.g., butyl rubber, neoprene, nitrile) when using or handling this product.										
8.6	Body Protection:	Not required under normal conditions of use are recommended when handling or using large quantities (e.g., > 5 gallons (18.9 L)) of this product.										

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Appearance:	Pink liquid.
9.2	Odor:	No odor
9.3	Odor Threshold:	NA
9.4	pH:	1.0
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	> 100 °C (> 212 °F)
9.7	Flashpoint:	NA
9.8	Upper/Lower Flammability Limits:	LEL: NA; UEL: NA
9.9	Vapor Pressure:	NA
9.10	Vapor Density:	> 1.0 (air = 1.0)
9.11	Relative Density:	1.012
9.12	Solubility:	Complete (water)
9.13	Partition Coefficient (log P _{ow}):	NA
9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	NA
9.17	Other Information:	Evaporation Rate: < 1.0 (ethyl ether = 1.0)

10. STABILITY & REACTIVITY

10.1	Stability:	Stable under normal storage and use conditions.
10.2	Hazardous Decomposition Products:	Thermal decomposition may produce carbon, potassium, sulfur and nitrogen oxides.
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Avoid high temperatures and incompatible materials.
10.5	Incompatible Substances:	Strong acids, water-reactive substances and metals such as aluminum and zinc.

11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: YES	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	Sodium Pyrophosphate, Dibasic: LD ₅₀ (oral, mouse) = 2,650 mg/kg; Sodium Xylene Sulfonate: LD ₅₀ (oral, rat) ≥ 7,200 mg/kg		
11.3	Acute Toxicity:	See Section 2.4		
11.4	Chronic Toxicity:	See Section 2.5		
11.5	Suspected Carcinogen:	NA		
11.6	Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans.		
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.		
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.		
	Teratogenicity:	This product is not reported to produce teratogenic effects in humans.		
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.		
11.7	Irritancy of Product:	See Section 2.3		
11.8	Biological Exposure Indices:	NE		
11.9	Physician Recommendations:	Treat symptomatically.		

12. ECOLOGICAL INFORMATION

12.1	Environmental Stability:	Phosphates may persist indefinitely if released into groundwater. Sodium Xylene Sulfonate: OECD Test Guideline 301B: 83-85% Readily biodegradable.
12.2	Effects on Plants & Animals:	No data available.
12.3	Effects on Aquatic Life:	No data available.

13. DISPOSAL CONSIDERATIONS



13.1	Waste Disposal:	Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations. Contact the appropriate agency for specific information. Treatment, transport, storage and disposal of hazardous waste must be provided by a licensed facility or waste hauler.
13.2	Special Considerations:	NA

14. TRANSPORTATION INFORMATION



The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):	NOT REGULATED
14.2	IATA (AIR):	NOT REGULATED
14.3	IMDG (OCN):	NOT REGULATED
14.4	TDGR (Canadian GND):	NOT REGULATED
14.5	ADR/RID (EU):	NOT REGULATED
14.6	SCT (MEXICO):	NOT REGULATED
14.7	ADGR (AUS):	NOT REGULATED

15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements:	This product does not contain any substances subject to SARA Title III, section 313 reporting requirements.	
15.2	SARA Threshold Planning Quantity:	NA	
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.	
15.4	CERCLA Reportable Quantity (RQ):	NA	
15.5	Other Federal Requirements:	NA	
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDL. None of the components of this product are listed on the Priorities Substances List. Class D2B (Materials Causing Other Toxic Effects).	
15.7	State Regulatory Information:	<p><u>Sodium Pyrophosphate, Dibasic</u> is found on the following state criteria lists: New Jersey Right-to-Know List (NJ), and Pennsylvania Right-to-Know List (PA).</p> <p>None of the ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).</p>	
15.8	Other Requirements:	<p>The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC. Harmful (C, Xn). <u>Risk Phrases</u> (R): R22-36/38 – Harmful if swallowed. Irritating to eyes and skin. <u>Safety Phrases</u> (S): S(2)-23-24-37/39-62 - Keep out of the reach of children. Do not breathe fumes/mists/vapors/spray. Avoid contact with skin. Wear suitable gloves and eye/face protection. If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label where possible.</p>	

16. OTHER INFORMATION

16.1	Other Information:	WARNING! MAY BE HARMFUL IN CONTACT WITH SKIN. CAUSES SKIN IRRITATION. CAUSES EYE IRRITATION. May be harmful in contact with skin. Causes skin irritation. Causes serious eye irritation. Wear protective gloves/eye protection. If swallowed, immediately call a Poison Center or doctor/physician. Avoid breathing mist/sprays. If skin irritation or rash occurs: Get medical advice/attention. KEEP OUT OF REACH OF CHILDREN.	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Precision Brand Products Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.	
16.4	Prepared for:	<p>Precision Brand Products, Inc. 2250 Curtiss Street Downers Grove, IL 60515 USA Tel: +1 (630) 969-7200 Fax: +1 (630) 969-0310 http://www.precisionbrand.com</p>	
16.5	Prepared by:	<p>ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com</p>	

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
----------------	----------------------------------

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
C	Ceiling Limit
IDLH	Immediately Dangerous to Life and Health
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
TLV	Threshold Limit Value

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
------------	--

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

HEALTH
FLAMMABILITY
PHYSICAL HAZARDS
PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

A	
B	
C	
D	
E	
F	

G	
H	
I	
J	
K	
X	Consult your supervisor or SOPs for special handling directions.

Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves
Boots	Synthetic Apron	Protective Clothing & Full Suit	Dust Respirator
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

ML	Maximum Limit
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD₁₀	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD₁₀, LD₁₀, & LD₅₀ or TC, TC₀, LC₁₀, & LC₅₀	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL_m	Median threshold limit
log K_{ow} or log K_{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful


CLP/GHS (1272/2008/EC) PICTOGRAMS:

Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment

1. PRODUCT & COMPANY IDENTIFICATION

1.1	Product Name:	PREVENT® NON-VOC FORMULA
1.2	Chemical Name:	Petroleum Distillate
1.3	Synonyms:	45119, 45116
1.4	Trade Names:	Prevent® Non-VOC Formula
1.5	Product Use:	Lubricate, Penetrate, Displace Water, Protect Surfaces from Corrosion
1.6	Distributor's Name:	Precision Brand Products, Inc.
1.7	Distributor's Address:	2250 Curtiss Street, Downers Grove IL 60515 USA
1.8	Emergency Phone:	ChemTrec +1 (800) 424-9300 / +1 (703) 527-3887 or Poison Control Center +1 (855) 281-1742
1.9	Business Phone / Fax:	+1 (630) 969-7200 / +1 (630) 969-0310

2. HAZARDS IDENTIFICATION

2.1	Hazard Identification:	<p>This product is classified as a hazardous substance but not as dangerous goods according to the classification criteria of [NOHSC: 1088 (2004)] and ADG Code (Australia).</p> <p>DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAY. MAY CAUSE AN ALLERGIC SKIN REACTION.</p> <p><u>Classification:</u> Asp. Tox. 1; Skin Sens. 1</p> <p><u>Hazard Statements (H):</u> H304 – May be fatal if swallowed and enters airways. H317 – May cause an allergic skin reaction.</p> <p><u>Precautionary Statements (P):</u> P280 – Wear protective gloves/eye protection. P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P301 – Do NOT induce vomiting. P261 Avoid breathing mist/sprays. P272 – Contaminated work clothing should not be allowed out of the workplace. P302+P352 – IF ON SKIN: Wash with plenty of soap and water. P333+P313 – If skin irritation or rash occurs: Get medical advice/attention. P321 – Specific treatment – see section 4 of this Safety Data Sheet. P363 Wash contaminated clothing before reuse. P405 – Store locked up. P501 - Dispose of contents/container to licensed treatment, storage and disposal facility (TSDF).</p>	
-----	------------------------	---	---

3. COMPOSITION & INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)									OTHER
					ACGIH		NOHSC			OSHA				
					ppm		ppm			ppm				
					TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	TLV	STEL	IDLH		
WHITE MINERAL OIL	8042-47-5	PY8047000	232-455-8	60-100	(5)	NA	(5)	NA	NA	(5)	(10) *	(2500) *	NIOSH	
Asp. Tox. 1; H304, H226														
SEVERELY HYDROTREATED NAPHTHENIC PETROLEUM OIL *	64742-52-5	NA	265-155-0	10-30	(5)	(10)	(5)	NA	NA	(5)	NA	NA	OIL MIST	
* contains less than 3% Dimethyl Sulfoxide														
BARIUM ALKYLNAPHTHALENE SULFATE	25619-56-1	NA	247-132-7	7-13	NA	NA	NF	NF	NF	NA	NA	NA		
Acute Tox. 4; Skin Irrit. 2; Skin Sens. 1; Eye Irrit. 2; H302, H315, H317, H319, H332														

4. FIRST AID MEASURES

4.1	First Aid:	<p><u>Ingestion:</u> DO NOT INDUCE VOMITING. Contact ChemTrec +1 (800) 424-9300 or the nearest Poison Control Center or local emergency telephone number for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.</p> <p><u>Eyes:</u> If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately.</p> <p><u>Skin:</u> Remove contaminated clothing and wash affected areas with soap and water. If discomfort persists and/or the skin reaction worsens, contact a physician immediately. Do not wear contaminated clothing until after it has been properly cleaned.</p> <p><u>Inhalation:</u> Remove victim to fresh air at once. Under extreme conditions, if breathing stops, perform artificial respiration. Seek immediate medical attention.</p>
4.2	Effects of Exposure:	<p><u>Eyes:</u> Irritation upon direct contact.</p> <p><u>Skin:</u> Irritation and possible dermatitis.</p> <p><u>Ingestion:</u> Irritation to the gastrointestinal tract. Aspiration of mineral oil into the lungs can cause chemical pneumonia.</p> <p><u>Inhalation:</u> Inhalation of high vapor concentrations may cause central nervous system effects, and symptoms such as headache, dizziness, and disorientation.</p>
4.3	Symptoms of Overexposure:	<p><u>Eyes:</u> Redness, burning, irritation, and swelling around eyes.</p> <p><u>Skin:</u> Redness, burning, itching, rash, and scaling of the skin (dermatitis).</p> <p><u>Ingestion:</u> Nausea, vomiting, severe abdominal pain.</p> <p><u>Inhalation:</u> Coughing, wheezing, swelling of throat, irritation in mucous membranes, difficulty breathing.</p>
4.4	Acute Health Effects:	May be fatal if swallowed and enters airways. May cause an allergic skin reaction. May be harmful if swallowed. Breathing of high vapor concentrations may cause headaches, stupor, irritation of throat and eyes, disorientation.

4. FIRST AID MEASURES – cont'd

4.5	Chronic Health Effects:	Prolonged or repeated skin exposure may cause dermatitis.			
4.6	Target Organs:	Eyes, Skin, Respiratory System, Lungs.			
4.7	Medical Conditions Aggravated by Exposure:	Persons with pre-existing central nervous system (CNS) disease, neurological conditions, skin disorders, chronic respiratory diseases, or impaired liver or kidney function should avoid exposure.	HEALTH		1
			FLAMMABILITY		1
			PHYSICAL HAZARDS		0
			PROTECTIVE EQUIPMENT		B
			EYES	SKIN	

5. FIREFIGHTING MEASURES

5.1	Fire & Explosion Hazards:	High heat will cause product to boil, evolving vapor that could cause explosive rupture of closed containers. Avoid all ignition sources such as sparks, heat and open flames. Product or residue can ignite explosively.	
5.2	Extinguishing Methods:	Carbon Dioxide, Foam, Low Velocity Water Fog, Halon (if permitted), Dry Chemical Extinguisher.	
5.3	Firefighting Procedures:	As with any fire, firefighters should wear appropriate protective equipment including a MSHA/NIOSH approved or equivalent self-contained breathing apparatus (SCBA) and protective clothing. Treat as hot oil. Hazardous decomposition products may be released. Thermal degradation may produce oxides of carbon, and/or nitrogen, hydrocarbons and/or derivatives. Fire should be fought from a safe distance. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway.	

6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	<p>Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment (PPE). Use safety glasses or safety goggles and face shield; use gloves and other protective clothing (e.g., apron, boots, etc.) to prevent skin contact.</p> <p><u>Small Spills:</u> Wear appropriate protective equipment including gloves and protective eyewear. Use a non-combustible, inert material such as vermiculite or sand to soak up the product and place into a container for later disposal.</p> <p><u>Large Spills:</u> Keep incompatible materials (e.g., organics such as oil) away from spill. Stay upwind and away from spill or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Use ONLY non-sparking tools. Wear appropriate protective equipment including respiratory protection as conditions warrant. Recover as much free liquid as possible and collect in acid-resistant container. Use absorbent to pick up residue. Avoid discharging liquid directly into a sewer or surface waters.</p>
-----	---------	--

7. HANDLING & STORAGE INFORMATION


7.1	Work & Hygiene Practices:	Avoid breathing mists or spray. Avoid eye and skin contact. Wear protective equipment when handling product. Keep out of the reach of children. Do not eat, drink or smoke when handling this product. Wash thoroughly after handling. Do not expose to heat and flame. Use only in ventilated areas. Immediately clean-up and decontaminate any spills or residues.
7.2	Storage & Handling:	Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Store in closed containers. Avoid temperatures above 40 °C (120 °F). Keep away from incompatible substances (see Section 10). Protect containers from physical damage.
7.3	Special Precautions:	Empty containers may retain hazardous product residues.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Exposure Limits: ppm (mg/m ³)	ACGIH			NOHSC			OSHA			OTHER			
		CHEMICAL NAME(S)				TLV	STEL	ES-TWA	ES-STEL	ES-PEAK		PEL	STEL	IDLH
		NA				NA	NA	NF	NF	NF	NA	NA	NA	
8.2	Ventilation & Engineering Controls:	Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).												
8.1	Ventilation & Engineering Controls:	Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).												
8.3	Respiratory Protection:	In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.												
8.4	Eye Protection:	Safety glasses with side shields must be used when handling or using this product. A protective face shield is also recommended.												



8. EXPOSURE CONTROLS & PERSONAL PROTECTION – cont'd

8.5	Hand Protection:	Wear protective, chemical-resistant gloves (e.g., neoprene) when using or handling this product.	
8.6	Body Protection:	Not required under normal conditions of use. A chemical resistant apron and/or protective clothing are recommended when handling or using large quantities (e.g., > 5 gallons (18.9 L)) of this product.	

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Appearance:	Opaque, light brown liquid
9.2	Odor:	Kerosene odor
9.3	Odor Threshold:	NA
9.4	pH:	NA
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	> 110 °C (> 230 °F)
9.7	Flashpoint:	120 °C (248 °F), open cup
9.8	Upper/Lower Flammability Limits:	LEL: NA; UEL: NA
9.9	Vapor Pressure:	NA
9.10	Vapor Density:	> 1.0 (air = 1.0)
9.11	Relative Density:	0.8057
9.12	Solubility:	Immiscible (water)
9.13	Partition Coefficient (log P _{ow}):	NA
9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	NA
9.17	Other Information:	Evaporation Rate: < 1.0 (ethyl ether = 1.0); VOC: 0.2 lbs/gallon

10. STABILITY & REACTIVITY

10.1	Stability:	Stable under normal storage and use conditions.
10.2	Hazardous Decomposition Products:	Thermal decomposition may produce carbon and nitrogen oxides, hydrocarbons and/or derivatives.
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Avoid high temperatures, ignition sources and incompatible materials.
10.5	Incompatible Substances:	Strong reducing agents, acids, alkalis, oxidizing agents.

11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: YES	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	Severely Hydrotreated Naphthenic Petroleum Oil (Mineral Oil): LD50 (oral, rat) > 5,000 mg/kg		
11.3	Acute Toxicity:	See Section 2.4		
11.4	Chronic Toxicity:	See Section 2.5		
11.5	Suspected Carcinogen:	IARC 3 (not classifiable as to carcinogenicity in humans (for mineral oils, highly refined))		
11.6	Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans.		
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.		
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.		
	Teratogenicity:	This product is not reported to produce teratogenic effects in humans.		
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.		
11.7	Irritancy of Product:	See Section 2.3		
11.8	Biological Exposure Indices:	NE		
11.9	Physician Recommendations:	Treat symptomatically.		

12. ECOLOGICAL INFORMATION

12.1	Environmental Stability:	This product is expected to have a low potential to degrade and thus is expected to persist in the environment. Do not allow to enter into soil/subsoil. If product enters soil, it will be mobile and may contaminate groundwater.
12.2	Effects on Plants & Animals:	No data available.
12.3	Effects on Aquatic Life:	No data available.

13. DISPOSAL CONSIDERATIONS



13.1	Waste Disposal:	Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations. Contact the appropriate agency for specific information. Treatment, transport, storage and disposal of hazardous waste must be provided by a licensed facility or waste hauler.
13.2	Special Considerations:	If incinerated, the resulting ash will contain extractable barium. A waste with extractable barium of 100 ppm or greater is assigned EPA Hazardous Waste Number D005 (Toxicity Characteristic – Barium).

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):	NOT REGULATED	
14.2	IATA (AIR):	NOT REGULATED	
14.3	IMDG (OCN):	NOT REGULATED	
14.4	TDGR (Canadian GND):	NOT REGULATED	
14.5	ADR/RID (EU):	NOT REGULATED	
14.6	SCT (MEXICO):	NOT REGULATED	
14.7	ADGR (AUS):	NOT REGULATED	

15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements:	This product does not contain any substances subject to SARA Title III, section 313 reporting requirements.	
15.2	SARA Threshold Planning Quantity:	NA	
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.	
15.4	CERCLA Reportable Quantity (RQ):	NA	
15.5	Other Federal Requirements:	NA	
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS Class D2B (Materials Causing Other Toxic Effects).	
15.7	State Regulatory Information:	<p><u>Severely Hydrotreated Naphthenic Petroleum Oil (Mineral Oil)</u> is found on the following state criteria lists: New Jersey Right-to-Know List (NJ), and Pennsylvania Right-to-Know List (PA).</p> <p>No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).</p>	
15.8	Other Requirements:	<p>The primary components of this product are listed in Annex I of EU Directive 67/548/EEC.</p> <p><u>Severely Hydrotreated Naphthenic Petroleum Oil (Mineral Oil)</u>: Harmful (Xn). <u>Risk Phrases (R)</u>: R36/37/38-65 – Irritating to eyes, respiratory system and skin. Harmful – may cause lung damage if swallowed. <u>Safety Phrases (S)</u>: S(2)-23-24-62 - Keep out of the reach of children. Do not breathe fumes/mists/vapors/spray. Avoid contact with skin. If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label where possible.</p>	

16. OTHER INFORMATION

16.1	Other Information:	DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAY. MAY CAUSE AN ALLERGIC SKIN REACTION. May cause an allergic skin reaction. Wear protective gloves/eye protection. If swallowed, immediately call a Poison Center or doctor/physician. Avoid breathing mist/sprays. If skin irritation or rash occurs: Get medical advice/attention. KEEP OUT OF REACH OF CHILDREN.
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Precision Brand Products Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.
16.4	Prepared for:	Precision Brand Products, Inc. 2250 Curtiss Street Downers Grove, IL 60515 USA Tel: +1 (630) 969-7200 Fax: +1 (630) 969-0310 http://www.precisionbrand.com 
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com 

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
----------------	----------------------------------

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
C	Ceiling Limit
IDLH	Immediately Dangerous to Life and Health
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
TLV	Threshold Limit Value

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
------------	--

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

HEALTH
FLAMMABILITY
PHYSICAL HAZARDS
PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

A	
B	
C	
D	
E	
F	

G	
H	
I	
J	
K	
X	Consult your supervisor or SOPs for special handling directions.

Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves
Boots	Synthetic Apron	Protective Clothing & Full Suit	Dust Respirator
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

ML	Maximum Limit
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD₁₀	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD₁₀, LD₁₀, & LD₅₀ or TC, TC₀, LC₁₀, & LC₅₀	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL_m	Median threshold limit
log K_{ow} or log K_{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment