

SECTION 1: PRODUCT AND COMPANY INFORMATION

Product Name:	Val-Sol Blue Layout Ink
Supplier:	ValCool, LLC 5230 Brittmoore Rd Houston, TX 77041
Telephone:	(800) 244-9004
Fax:	(888) 695-6449
Email:	support@valcool.com
In case of Emergency:	CHEMTREC 800-424-9300
Product Description	Blue Layout Ink

SECTION 2: HAZARD IDENTIFICATION

GHS Classification

Flammable Aerosol – 1
Gas Under Pressure – Liquefied Gas
Eye Damage/Irritation – 2A
Carcinogenicity – 1A
Reproductive Toxin – 1A

GHS Label

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictogram



Signal word Danger

Hazard Statement Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes serious eye irritation.
May cause cancer.
May damage fertility or the unborn child.

Precautionary statements

Prevention Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces – No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container – Do not pierce or burn, even after use.
Wash hands thoroughly after handling.



Name: Val-Sol Blue Layout Ink
Revision Date: 7/11/2018 – R1

ValCool, LLC
5230 Brittmoore Rd
Houston, TX 77041

Wear protective gloves/protective clothing/eye protection/face protection.
Use personal protective equipment as required.
IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
IF exposed or concerned: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Store locked up.
Protect from sunlight. Store in a well ventilated place.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Components/Ingredients	CAS No.	%
Acetone	67-64-1	58.00
Propane	74-98-6	18.00
Isobutylacetate	110-19-0	7.20
Toluene	108-88-3	5.00
Isopropylalcohol	67-63-*0	2.20
Ethyl 3-Ethoxypropionate	763-69-9	1.30
Xylene, Mixed Isomers	1330-20-7	1.20
Ethylalcohol, Ethanol	64-17-5	1.10
Ethylbenzene	100-41-4	0.25

SECTION 4: FIRST AID MEASURES

Eye Contact Wash immediately with large volumes of fresh water for at least 15 minutes. Get medical attention.

Skin Contact Wipe off with a towel. Wash with soap and water. Get medical attention if irritation persists.

Ingestion Not a likely route of exposure

Inhalation Remove to fresh air. Administer oxygen if needed. Apply artificial respiration if breathing has stopped. Get medical attention.

Information for doctor:



Name: Val-Sol Blue Layout Ink
Revision Date: 7/11/2018 – R1

ValCool, LLC
5230 Brittmoore Rd
Houston, TX 77041

Most important symptoms/effects, acute and delayed	Repeated exposure may cause skin dryness or cracking. May cause drowsiness or dizziness.
Description of necessary first aid measures / specific treatments	None Known.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing Media

Suitable extinguishing agents Foam, Alcohol foam, CO2, Dry chemical, Water fog.

Unsuitable Extinguishing Media Water spray may be ineffective.

Special hazards arising from the substance or mixture	Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Liquid content of container will support combustion. Overexposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain medical attention. Hazardous decomposition products include carbon dioxide, carbon monoxide, and other toxic fumes.
---	--

Special Fire Fighting Instructions

Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat. Wear goggles and use self-contained breathing apparatus. If water is used, fog nozzles are preferred.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment & emergency procedures	Avoid breathing vapors. Ventilate area. Remove all sources of ignition.
--	---

Methods and materials for containment and cleaning up	Clean up with absorbent material and place in closed containers for disposal.
--	---

SECTION 7: HANDLING AND STORAGE

Handling

Precautions for safe handling	Do not puncture or incinerate (burn) cans. Do not stick pins, nails, or any other sharp objects into opening on top of can. Do not spray in eyes. Do not take internally. See product label for additional information.
-------------------------------	---



Name: Val-Sol Blue Layout Ink
Revision Date: 7/11/2018 – R1

ValCool, LLC
5230 Brittmoore Rd
Houston, TX 77041

Storage

Conditions for safe storage, including any incompatibilities Store and use in cool, dry, well-ventilated areas. Do not store above 120 F.

SECTION 8: EXPOSURE CONTROL AND PERSONAL PROTECTION

Control parameters

Components with limit values that require monitoring at the workplace

Acetone	67-64-1
OSHA	PEL-TWA: 750 ppm;
ACGIH	TLV-TWA: 500 ppm;
	TLV-STEL: 750 ppm
Propane	74-98-6
OSHA	Not established
ACGIH	TWA: 1000 ppm
Isobutylacetate	110-19-0
OSHA	PEL: 150 ppm
ACGIH	TLV: 150 ppm
Toluene	108-88-3
OSHA	TWA: 200 ppm 8 Hour;
	CEIL: 300 ppm;
	PEAK: 500 ppm 10 Minutes
ACGIH	TWA: 20 ppm 8 hour
Isopropylalcohol	67-63-0
OSHA	PEL-TWA: 400 ppm;
	PEL-Ceiling: Not determined
ACGIH	TLV-TWA: 200 ppm;
	TLV-STEL: 400 ppm
Ethyl 3-ethoxypropionate	763-69-9
OSHA	
ACGIH	
Other Exposure Limits	TWA: 50 ppm (Eastman);
	STEL: 100 ppm (Eastman)
Xylene, Mixed Isomers	1330-20-7
OSHA	PEL: 100 ppm
ACGIH	TLV: 100 ppm;
	STEL: 150 ppm, 15 Minutes

Ethylalcohol Ethanol 64-17-5
OSHA PEL-TWA: 1000 ppm;
PEL-Ceiling: Not established
ACGIH TLV-TWA: 1000 ppm;
TLV-STEL: Not established

Ethylbenzene 100-41-4
OSHA TWA: 100 ppm, 8 Hour
ACGIH TWA: 100 ppm, 8 Hour;
STEL: 125 ppm, 8 Hour

Additional information: The lists that were valid during the creation were used as basis

Appropriate engineering controls: Ventilation should be sufficient to prevent inhalation of any vapors. General dilution and/or local exhaust ventilation in volume to keep PEL/TLV of most hazardous ingredient below acceptable limit and IEL below stated limit.

Exposure controls

Personal protective equipment

Eye / Face Protection



None under normal use. However, use of safety glasses with splash guards or full face shield should be used if indicated.

Hand Protection



Protective Gloves

None under normal use. Use solvent-resistant for prolonged or repeated contact.

Respiratory Protection

None under normal use. Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use an approved air-line respirator or hood. Self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

Other protective clothing or equipment

None under normal use. However, use of solvent-resistant aprons or other clothing is recommended. Eye washes and safety showers in the workplace are recommended.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Aerosol product
Vapor Pressure	Not determine
Vapor Density	Heavier than air
Density	Not determined
Freezing Point	Not determined
Boiling Point	Not determined
Evaporation Rate	Slower than ether



Name: Val-Sol Blue Layout Ink
Revision Date: 7/11/2018 – R1

ValCool, LLC
5230 Brittmoore Rd
Houston, TX 77041

Explosive Limits	Not applicable
Decomposition Temperature	Not determined
Partition Coefficient	Not determined
Odor	Solvent
Odor Threshold	Not determined
pH	Not applicable
Melting Point	Not determined
Solubility	Not determined
Flash Point	Not determined
Flammability	Level 2 Aerosol
Autoignition Temperature	Not determined
Viscosity	Not determined

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Not reactive under normal conditions of use.
Chemical Stability	Stable under normal storage and handling conditions.
Possibility of hazardous reactions	Not known.
Incompatibility with other Materials	Acids, Bases, Strong oxidizing agents
Hazardous decomposition materials	Carbon dioxide, carbon monoxide, smoke, fumes, and other products of incomplete combustion.

SECTION 11: TOXICOLOGICAL INFORMATION

Long-term toxicological studies have not been conducted for this product.

SECTION 12: ECOLOGICAL INFORMATION

Long-term ecological studies have not been conducted for this product.

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state, and federal regulations. Before attempting clean up, refer to other sections of this document for hazard cautionary information.



Name: Val-Sol Blue Layout Ink
Revision Date: 7/11/2018 – R1

ValCool, LLC
5230 Brittmoore Rd
Houston, TX 77041

SECTION 14: TRANSPORT INFORMATION

By Land: DOT Proper Shipping Name: None required per 49 CFR 173.306 (i) for products that conform to the Limited Quantity provisions. Commodity shipping description: Cleaning Compound, NOI.

By Water: DOT & IMDG Proper Shipping Name: UN1950, Aerosols, 2.1, LTD QTY.

By Air: DOT & IATA Proper Shipping Name: UN1950, Aerosols, flammable, 2.1, LTD QTY (packing instruction Y203 applies)

SECTION 15: REGULATORY INFORMATION

All ingredients are either listed on the TSCA inventory or are exempt.

SECTION 16: OTHER INFORMATION

Revision Date: 7/11/2018 - 1

Abbreviations and acronyms:

DOT: US Department of Transportation
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Skin Sens. 1B: Sensitization - Skin, Hazard Category 1B

HMIS:

Disclaimer: The information presented herein has been compiled from sources considered to be dependable and is accurate as of the date issued. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use are beyond our control, we make no warranty regarding the accuracy of such data or its suitability for any use or for any consequence of its use. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. Safe handling and use remains the responsibility of the purchaser and the purchaser has the sole responsibility to determine the suitability of the materials for any use and the manner of user contemplated. We assume no responsibility for injury to the recipient or to third persons or for any damage to any property and the recipient assumes all such risks.