

ValCool, LLC 5230 Brittmoore Rd Houston, TX 77041

# SECTION 1: PRODUCT AND COMPANY INFORMATION

Product Name:	Val-Sol Red Spray Grease
Supplier:	ValCool, LLC 5230 Brittmoore Rd Houston, TX77041
Telephone: Fax: Email:	(800) 244-9004 (888) 695-6449 <u>support@valcool.com</u>
In case of Emergency:	CHEMTREC 800-424-9300

#### **Product Description**

All purpose red spray grease

## **SECTION 2: HAZARD IDENTIFICATION**

## **GHS Classification**

Flammable aerosol – 1 Gas under pressure – Liquefied gas Skin Corrosion/Irritation – 4 Eye Damage/Irritation – 2B

GHS LabelGHS label elements The product is classified and labeled according to the<br/>Globally Harmonized System (GHS).

Hazard pictogram



Signal word Danger

Hazard Statement Extremely flammable aerosol Extremely flammable liquid and vapor Contains gas under pressure: may explode if heated Causes eye irritation May be harmful if inhaled

### **Precautionary statements**

Prevention Do not spray on an open flame or other ignition source. Pressurized container – Do not pierce or burn, even after use Avoid breathing dust/fume/gas/mist/vapors/spray Wash hands thoroughly after handling Use only outdoors or in a well-ventilated area Wear protective gloves/protective clothing/eye protection/face protection



ValCool, LLC 5230 Brittmoore Rd Houston, TX 77041

 Response Wash hands thoroughly after handling.
Call a POISON CENTER or doctor/physician if you feel unwell IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing If eye irritation persists: Get medical advice/attention
Storage Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

# SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Components/Ingredients	CAS No.	%
Naphtha (Petroleum), Hydrotreated Light	64742-49-00	50.6
Propane	74-98-6	15.0

# **SECTION 4: FIRST AID MEASURES**

Eye Contact	Wash immediately with large volumes of fresh water for at least 15 minutes. Get medical attention.
Skin Contact	Wipe off with a towel. Wash with soap and water. Get medical attention if irritation persists.
Ingestion	Not a likely route of exposure.
Inhalation	Remove to fresh air. Administer oxygen if needed. Apply artificial respiration if breathing has stopped. Get medical attention.

Information for doctor:

Most important symptoms/effects, acute and delayed	Repeated exposure may cause skin dryness or cracking. May cause drowsiness or dizziness.
Description of necessary first aid measures / specific treatments	None Known.



# **SECTION 5: FIREFIGHTING MEASURES**

## **Extinguishing Media**

Suitable extinguishing agents	Foam, Alcohol foam, CO2, Dry chemical, Water fog.
Unsuitable extinguishing agents	Water spray may be ineffective.
Special hazards arising from the substance or mixture	Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Liquid content of container will support combustion. Overexposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain medical attention. Hazardous decomposition products include carbon dioxide, carbon monoxide, and other toxic fumes.
Special Fire Fighting Instructions	Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat. Wear goggles and use self-contained breathing apparatus. If water is used, fog nozzles are preferred.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment & emergency procedures	Avoid breathing vapors. Ventilate area. Remove all sources of ignition.
Methods and materials for containment and cleaning up	Clean up with absorbent material and place in closed containers for disposal.

# **SECTION 7: HANDLING AND STORAGE**

## Handling

Precautions for safe handling	Do not puncture or incinerate (burn) cans. Do not stick pins, nails, or
	any other sharp objects into opening on top of can. Do not spray in eyes. Do not take internally. See product label for additional information.

# Storage

Conditions for safe storage,	5
including any incompatibilities	[

Store and use in cool, dry, well-ventilated areas. Do not store above 120 F.



ValCool, LLC 5230 Brittmoore Rd Houston, TX 77041

# SECTION 8: EXPOSURE CONTROL AND PERSONAL PROTECTION

## Additional information about design of technical systems - No further data; see item 7.

### **Control parameters**

Components with limit values that require monitoring at the workplace

Naphtha (Petroleum), Hydrotreated Light	64742-49-0
OSHA	TWA: 500 ppm PEL-Ceiling: Not determined
ACGIH	TLV-TWA: 400 ppm TLV-STEL: 500 ppm
Propane	74-98-6
OSHA	Not established
ACGIH TWA:	1000 ppm
Appropriate engineering controls	Ventilation should be sufficient to preven

Ventilation should be sufficient to prevent inhalation of any vapors. General dilution and/or local exhaust ventilation in volume to keep PEL/TLV of most hazardous ingredient below acceptable limit and lel below stated limit.

# Exposure controls Personal protective equipment

Eye / Face Protection

Hand Protection

Respiratory Protection

Other protective clothing or equipment



None under normal use. However, use of safety glasses with splash guards or full face shield should be used if indicated.

### **Protective Gloves**

None under normal use. Use solvent-resistant for prolonged or repeated contact.

None under normal use. Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination or particles and vapor. In confined areas, use an approved air-line respirator or hood. Self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

None under normal use. However, use of solvent- resistant aprons or other clothing is recommended. Eye washes and safety showers in the workplace are recommended.



ValCool, LLC 5230 Brittmoore Rd Houston, TX 77041

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	Aerosol product
Vapor Pressure	Not determine
Vapor Density	Heavier than air
Density	0.71
Freezing Point	Not determined
Boiling Point	93°C
Evaporation Rate	Slower than ether
Explosive Limits	Not applicable
Autoignition Temperature	Not determined
Viscosity	Not determined
Odor	Solvent
Odor Threshold	Not determined
рН	Not applicable
Melting Point	Not determined
Solubility	Not determined
Flash Point	-157°F
Flammability	Level 3 Aerosol
Partition Coefficient (n- octanal/water)	Not determined
Decomposition Temperature	Not determined

# SECTION 10: STABILITY AND REACTIVITY

Reactivity	Not reactive under normal conditions of use.
Chemical Stability	Stable under normal storage and handling conditions.
Possibility of hazardous reactions	None known.
Incompatibility with other Materials	None known.
Hazardous decomposition materials	Carbon dioxide, carbon monoxide, and other toxic fumes.



ValCool, LLC 5230 Brittmoore Rd Houston, TX 77041

# SECTION 11: TOXICOLOGICAL INFORMATION

Long-term toxicological studies have not been conducted for this product.

# **SECTION 12: ECOLOGICAL INFORMATION**

Long-term ecological studies have not been conducted for this product.

# **SECTION 13: DISPOSAL CONSIDERATIONS**

Dispose of in accordance with local, state, and federal regulations. Before attempting clean up, refer to other sections of this document for hazard cautionary information.

# **SECTION 14: TRANSPORT INFORMATION**

**By land**: DOT Proper Shipping Name: None required per 49 CFR 173.306(i) for products that conform to the Limited Quantity provisions. Commodity shipping description: Lubricant, NOI

By water: DOT & IMDG Proper Shipping Name: UN1950, Aerosols, 2.1, LTD QTY

**By air**: DOT & IATA Proper Shipping Name: UN1950, Aerosols, flammable, 2.1, LTD QTY (packing instruction Y203 applies)

# **SECTION 15: REGULATORY INFORMATION**

All ingredients are either listed on the TSCA inventory or are exempt.

# **SECTION 16: OTHER INFORMATION**

## **Revision Date**: 7/21/2018 - 1

#### Abbreviations and acronyms:

DOT: US Department of Transportation ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)



ValCool, LLC 5230 Brittmoore Rd Houston, TX 77041

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Skin Sens. 1B: Sensitization - Skin, Hazard Category 1B

# HMIS:

**Disclaimer**: The information presented herein has been compiled from sources considered to be dependable and is accurate as of the date issued. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use are beyond our control, we make no warranty regarding the accuracy of such data or its suitability for any use or for any consequence of its use. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. Safe handling and use remains the responsibility of the purchaser and the purchaser has the sole responsibility to determine the suitability of the materials for any use and the manner of user contemplated. We assume no responsibility for injury to the recipient or to third persons or for any damage to any property and the recipient assumes all such risks.