



# Material Safety Data Sheet

## 1. Chemical Product and Company Identification

DESCRIPTION: PROBOND PROFESSIONAL CONTACT CEMENT  
PRODUCT TYPE: SYNTHETIC RUBBER SOLUTION  
APPLICATION: E531, 60532

### • Manufacturer/Supplier Information

MSDS Prepared by:  
Elmer's Products, Inc.  
1 Easton Oval  
Columbus, OH 43219

Emergency Phone Number  
Poison Control Center  
888-516-2502

For additional health, safety or regulatory information, call 888-435-6377.  
Call 1-800-848-9400 to place an order or request additional MSDSs.

## 2. Composition, Information on Ingredients

The ingredients listed below have been associated with one or more immediate and/or delayed(\*) health hazards. Risk of damage and effects depends upon duration and level of exposure. BEFORE USING, HANDLING, OR EXPOSURE TO THESE INGREDIENTS, READ AND UNDERSTAND THE MSDS.

	% by weight
78-93-3 *Methyl Ethyl Ketone	10-30
109-60-4 *n-Propyl Acetate	10-30
64742-89-8 Light Aliphatic Solvent Naphtha (petroleum)	30-50

## 3. Hazards Identification

### 3.1 Emergency Overview

Appearance Yellow tan medium syrup  
Odor Petroleum

#### WARNING!

FLAMMABLE LIQUID AND VAPOR

Causes eye irritation.

Overexposure may cause central nervous system depression. May cause irritation of nose, throat and lungs if allowed to become airborne.

### • HMIS Rating

HEALTH = 2 (moderate)  
FLAMMABILITY = 3 (serious)

## 3.2 Potential Health Effects

---

- **Immediate Hazards**

INGESTION: No hazards known to company.

INHALATION: Not expected to be harmful under normal conditions of use. However, overexposure may cause central nervous system depression. Also, if allowed to become airborne, may cause irritation of nose, throat and lungs.

SKIN: May cause irritation on prolonged or repeated contact.

EYES: Causes irritation.

Methyl Ethyl Ketone 78-93-3

Can cause central nervous system depression. Signs and symptoms may include headache, dizziness, nausea, vomiting, unconsciousness and asphyxiation. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may lead to addiction and may be harmful or fatal.

n-Propyl Acetate 109-60-4

Can cause central nervous system depression. Signs and symptoms may include headache, dizziness, nausea, vomiting, unconsciousness and even asphyxiation.

Light Aliphatic Solvent Naphtha (petroleum) 64742-89-8

Can cause central nervous system depression. Signs and symptoms may include headache, dizziness, nausea, vomiting, unconsciousness and even asphyxiation.

---

- **Delayed Hazards**

Methyl Ethyl Ketone 78-93-3

Suspect reproductive hazard. May cause reproductive disorders based on animal data.

Methyl ethyl ketone may potentiate (shorten the time of onset) peripheral neuropathy caused by methyl n-butyl ketone or n-hexane.

Methyl ethyl ketone by itself has not been shown to cause peripheral neuropathy.

-- See Footnote C.

n-Propyl Acetate 109-60-4

May cause liver damage based on animal data.

-- See Footnote C.

Footnote C: As of the date of issuance of this document, this material has not been listed by NTP, classified by IARC nor regulated by OSHA as a carcinogen.

---

## 4. First Aid Measures

INGESTION: If accidentally swallowed, dilute by drinking large quantities of water. Immediately contact poison control center or hospital emergency room for any other additional treatment directions.

INHALATION: Remove to fresh air.

SKIN: In case of irritation, flush with water.

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held apart during irrigation to insure water contact with entire surface of eyes and lids. Call a physician.

---

## 5. Fire Fighting Measures

Autoignition Temperature	Not available
Upper/Lower Flammable Limits	Not available
Up/Lower Explosive Limits, % by Vol	10/0.9
Flash Point	> -7 deg C

FLAMMABLE.

Keep liquid and vapor away from heat, sparks, flame and other ignition sources including, but not limited to, pilot lights, heaters, cigarettes, electric motors and static discharge. Vapor is heavier than air and may settle in low places or travel outward to a source of ignition and flashback.

In case of fire, use water spray, dry chemical, foam or CO<sub>2</sub>. Use water to keep fire-exposed containers cool.

---

## 6. Accidental Release Measures

Eliminate all ignition sources. Sweep (scoop) up and remove to a chemical disposal area. Prevent entry into natural bodies of water.

---

## 7. Handling and Storage

---

### 7.1 Handling

Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of the material from eyes, skin and clothing.

Wash thoroughly after handling. Always use appropriate Personal Protective Equipment (PPE).

INHALATION: Avoid prolonged or repeated breathing of vapor.

SKIN: Persons with sensitive skin should avoid prolonged, continuous contact with skin. If irritation develops, discontinue use.

EYES: Avoid contact with eyes.

---

### 7.2 Storage

Store in a cool, dry place.

Keep containers tightly closed.

Keep away from heat, sparks, flame and other ignition sources.

---

## 8. Exposure Controls/Personal Protection

---

### 8.1 Exposure Controls

ENGINEERING CONTROLS: The following exposure control techniques may be used to effectively minimize employee exposure: local exhaust ventilation, enclosed system design, process isolation and remote control in combination with appropriate use of personal protective equipment and prudent work practices. These techniques may not necessarily address all issues pertaining to your operations. We, therefore, recommend that you consult with experts of your choice to

determine whether or not your programs are adequate. If airborne contaminants are generated when the material is heated or handled, sufficient ventilation in volume and air flow patterns should be provided to keep air contaminant concentration levels below acceptable criteria.

---

## 8.2 Personal Protection

Where air contaminants can exceed acceptable criteria, use NIOSH/MSHA approved respiratory protection equipment. Respirators should be selected based on the form and concentration of contaminants in air in accordance with OSHA laws and regulations or other applicable standards or guidelines, including ANSI standards regarding respiratory protection.

---

## 8.3 Exposure Guidelines

Methyl Ethyl Ketone                    78-93-3  
ACGIH TLV: 200 ppm (590 mg/m<sup>3</sup>) TWA; 300 ppm (885 mg/m<sup>3</sup>) STEL  
OSHA PEL: 200 ppm (590 mg/m<sup>3</sup>) TWA  
REMANDED PEL: 200 ppm (590 mg/m<sup>3</sup>) TWA; 300 ppm (885 mg/m<sup>3</sup>) STEL  
OSHA 1989 PEL remanded, but in effect in some states  
n-Propyl Acetate                    109-60-4  
ACGIH TLV: 200 ppm (835 mg/m<sup>3</sup>) TWA; 250 ppm (1040 mg/m<sup>3</sup>) STEL  
OSHA PEL: 200 ppm (840 mg/m<sup>3</sup>) TWA  
REMANDED PEL: 200 ppm (840 mg/m<sup>3</sup>) TWA; 250 ppm (1050 mg/m<sup>3</sup>) STEL  
OSHA 1989 PEL remanded, but in effect in some states  
Light Aliphatic Solvent Naphtha (petroleum)                    64742-89-8  
ACGIH TLV: NONE ESTABLISHED  
OSHA PEL: NONE ESTABLISHED

---

## 9. Physical and Chemical Properties

Percent Volatiles	82
pH @ 25 C	Not available
Specific Gravity	0.86
Appearance	Yellow tan medium syrup
Autoignition Temperature	Not available
Boiling Point	80 deg C
Vapor Density (Air=1)	> 1
Vapor Pressure, mm Hg @ 20 C	45
Evaporation Rate (Butyl Acetate=1)	> 1
Upper/Lower Flammable Limits	Not available
Up/Lower Explosive Limits, % by Vol	10/0.9
Flash Point	> -7 deg C
Freezing Point	Not available
Odor	Petroleum
Odor Threshold, ppm	Not available
Solubility in Water	Negligible
Coefficient of Water/Oil Distrib.	Not applicable

---

## 10. Stability and Reactivity

Normally stable as defined in NFPA 704-12(4-3.1).

---

- **Incompatibilities:**

Oxidizers, acids or bases.

---

- **Decomposition products may include:**

CO, CO2.

---

- **Hazardous polymerization:**

Will not occur.

---

- **Other Hazards:**

None known to company.

---

## 11. Toxicological Information

INGESTION: Not toxic orally when tested as described in 16 CFR Part 1500.3 (c)(1) and (2).  
INHALATION: Not toxic by inhalation when tested as described in 16 CFR Part 1500.3 (c)(1) and (2).  
SKIN ABSORPTION: Not toxic dermally when tested as described in 16 CFR Part 1500.3 (c)(1) and (2).  
SKIN: Not a primary irritant (primary skin irritation index less than 5.0/8.0) when tested as described in 16 CFR Part 1500.41.  
EYES: Moderately irritating when tested as described in 16 CFR Part 1500.42.

Methyl Ethyl Ketone 78-93-3  
LC50: Not available  
LD50: orl-rat=6.86 ml/kg (Merck)  
n-Propyl Acetate 109-60-4  
LC50: Not available  
LD50: orl-rat=9370 mg/kg (Merck)  
Light Aliphatic Solvent Naphtha (petroleum) 64742-89-8  
LC50: Not available  
LD50: Not available

---

## 12. Ecological Information

Not determined.

---

## 13. Disposal Considerations

Dispose of according to local, state/provincial, and federal requirements.  
Empty container: May contain explosive vapors. DO NOT cut, puncture or weld on or nearby.

---

## 14. Transport Information

---

### 14.1 U.S. Department of Transportation (DOT)

The data provided in this section is for information only and may not

be specific to your package size. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

ORM-D Consumer Commodity.

---

## 14.2 Canadian Transportation of Dangerous Goods (TDG)

Not determined.

---

## 15. Regulatory Information (Selected Regulations)

---

### 15.1 U.S. Federal Regulations

---

- **OSHA Hazard Communication Standard 29CFR1910.1200**

This material is a "health hazard" and/or a "physical hazard" as determined when reviewed according to the requirements of the Occupational Safety and Health Administration 29 CFR Part 1910.1200 "Hazard Communication" Standard.

---

- **SARA Title III: Section 311/312**

Fire hazard  
Immediate health hazard  
Delayed health hazard

---

- **SARA Title III Section 313 and 40 CFR Part 372**

This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986, and Subpart C-Supplier Notification Requirement of 40 CFR Part 372.

Methyl Ethyl Ketone

78-93-3 12.30%

---

- **TSCA Section 8(b) Inventory**

All reportable chemical substances are listed on the TSCA Inventory. We rely on certifications of compliance from our suppliers for chemical substances not manufactured by us.

---

### 15.2 Canadian Regulations

---

- **Workplace Hazardous Materials Information System (WHMIS)**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation (CPR) and the MSDS contains all the information required by the CPR.

- **Canadian Environmental Protection Act (CEPA)**

All reportable chemical substances are listed on the Domestic Substances List (DSL) or otherwise comply with CEPA new substance notification requirements.

---

- **National Pollutant Release Inventory (NPRI)**

This product contains the following chemical(s) subject to the reporting requirements of the Canadian Environmental Protection Act (CEPA) subsection 16(1), National Pollutant Release Inventory.

Methyl ethyl ketone	78-93-3	12.30%
---------------------	---------	--------

---

## 16. Other Information

HL (Cautions Required): Products bearing the HL Health Label (Cautions Required) Seal of The Art & Creative Materials Institute, Inc. (ACMI) are certified to be properly labeled in a program of toxicological evaluation by a medical expert. This program is reviewed by ACMI's Toxicological Advisory Board. These products are certified by ACMI to be labeled in accordance with the chronic hazard labeling standard, ASTM D-4236 and Federal Law, P.L. 100-695.

---

- **User's Responsibility**

The OSHA Hazard Communication Standard 29CFR 1910.1200 and the Workplace Hazardous Materials Information System (WHMIS) require that the information contained on these sheets be made available to your workers. Educate and train your workers regarding OSHA and WHMIS precautions. Instruct your workers to handle this product properly. Consult with appropriate experts to guard against hazards associated with use of this product and its ingredients.

---

- **Disclaimer**

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE, except that the product shall conform to contracted specifications, and that the product does not infringe any valid United States or Canadian patent. No claim of any kind shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. In no event shall Seller be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise.

---

CURRENT ISSUE: 23-JAN-07  
PREVIOUS ISSUE: 14-APR-04